30" M SERIES PROFESSIONAL SPEED OVEN

MOLF

SPO30PM/S/PH

FEATURES

Combines microwave, convection, and broil technologies to provide all-inone oven versatility

Provides more cooking power than a traditional microwave with the help of convection and broil

Assures predictably delicious results with 10 microwave power levels, convenient quick-start modes, and an intuitive Gourmet mode

Fits a 9-by-13 pan in the 1.6 cubic feet, stainless-steel interior

Micro Bake and Micro Roast modes reduce or completely eliminate preheat times

Frees up counter space with efficient drop-down door design

Coordinates with other Wolf built-in ovens and appliances with various handle and trim options


Master your technique with tips and recipes from the Mastering the Speed Oven guide



PRODUCT SPECIFICATIONS


Dimensions29 7/8"W x 17 7/8"H x 21 1/2"DCapacity1.6 cu. ft.Door Clearance14 3/16"Weight82 lbsElectrical Supplygrounded, 240/208 VAC, 60 HzElectrical Service15 amp dedicated circuitPower Cord Length6 FeetReceptacleNEMA 6-20R grounding type	Model	SPO30PM/S/PH
Door Clearance 14 3/16" Weight 82 lbs Electrical Supply grounded, 240/208 VAC, 60 Hz Electrical Service 15 amp dedicated circuit Power Cord Length 6 Feet	Dimensions	29 7/8"W x 17 7/8"H x 21 1/2"D
Weight 82 lbs Electrical Supply grounded, 240/208 VAC, 60 Hz Electrical Service 15 amp dedicated circuit Power Cord Length 6 Feet	Capacity	1.6 cu. ft.
Electrical Supply grounded, 240/208 VAC, 60 Hz Electrical Service 15 amp dedicated circuit Power Cord Length 6 Feet	Door Clearance	14 3/16"
Electrical Service 15 amp dedicated circuit Power Cord Length 6 Feet	Weight	82 lbs
Power Cord Length 6 Feet	Electrical Supply	grounded, 240/208 VAC, 60 Hz
	Electrical Service	15 amp dedicated circuit
Receptacle NEMA 6-20R grounding type	Power Cord Length	6 Feet
	Receptacle	NEMA 6-20R grounding type


ELECTRICAL




NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS






STANDARD INSTALLATION



TOP VIEW



SIDE VIEW

FRONT VIEW

NOTE: 24" (610) and 30" (762) models require the same opening dimensions.

⁻⁰ 17¹¹/16"